

Product Data Sheet

AQUA-X™ PRIMER

DESCRIPTION

- An ultra-premium grade acrylic based coating formulated to provide excellent adhesion to Zinalume®.

BENEFITS

- Quick drying.
- Good spray characteristics.
- Excellent adhesion to Zinalume®.
- Water-based – easy clean up and lower odour.

RECOMMENDED USE

- Recommended for applications where a hard and/or fast drying water-based coating is required.
- Suitable for use on most architectural and construction materials including concrete, masonry, primed steel, Zinalume®, etc.

BASIC DATA

- **APPLICATION:** Brush and spray
- **COVERAGE RATE:** 14 square metres per litre – will vary depending on substrate
- **GLOSS LEVEL:** Low Sheen
- **THINNER:** Not generally required - up to 10% with water
- **CLEAN UP:** Water – brushes and spray equipment must be cleaned immediately with water before the product has a chance to dry.
Clean brushes between coats.
- **RE-COAT:** 20-30 minutes (depending on conditions)
- **COLOUR RANGE:** Grey, White

SURFACE PREPARATION

- Surfaces must be clean, dry, and free of dust, grease, oils and wax.
- Loose powdery surfaces should be brushed down thoroughly and (if required) sealed with Gem™ Multi Purpose Undercoat prior to application of Aqua-X™.
- **DO NOT APPLY IF TEMPERATURE IS LESS THAN 10°C OR GREATER THAN 35°C OR IF RAIN IS ANTICIPATED WITHIN 12 HOURS.**

INSTRUCTIONS FOR USE

- Apply 1 coat of Aqua-X™ Primer. May be over-coated after approximately 30 minutes (@ 25°C).

SAFETY

- Provide adequate ventilation during use.
- Avoid contact with skin and eyes.
- Do not pour left over paint down any drains.
- **FIRST AID:** If swallowed, give plenty of water to drink and seek medical attention.
If in eyes, rinse with lots of water for at least 15 minutes – seek medical assistance.
If skin contact occurs, wash with warm soapy water – contact a doctor of irritation persists.