

Product Data Sheet

AQUA-X™ UV Clear

DESCRIPTION

- An ultra-premium grade acrylic based clear coating suitable for exterior timber surfaces.

BENEFITS

- Non-yellowing.
- UV Resistant.
- Good gloss retention.
- Water-based – easy clean up and lower odour.

RECOMMENDED USE

- As a clear finish for exterior wood surfaces.
- Not recommended for use on rough sawn timber.
- **Not recommended for use on timber floors or decks.**

BASIC DATA

- **APPLICATION:** Brush and spray
- **COVERAGE RATE:** 14 square metres per litre – will vary depending on substrate
- **GLOSS LEVEL:** Gloss
- **THINNER:** Not generally required - up to 10% with water
- **CLEAN UP:** Water – brushes and spray equipment must be cleaned immediately with water before the product has a chance to dry.
Clean brushes between coats.
- **RE-COAT:** 2 hours (depending on conditions)

SURFACE PREPARATION

- Surfaces must be clean, dry, and free of dust, grease, oils and wax.
- **DO NOT APPLY IF TEMPERATURE IS LESS THAN 10°C OR GREATER THAN 35°C.**

INSTRUCTIONS FOR USE

- Apply 1 coat of Aqua-X™ UV Clear and allow to dry.
- Lightly sand with fine abrasive – remove dust then apply at least 2 further coats for best results or until desired finish is achieved.

SAFETY

- Provide adequate ventilation during use.
- Avoid contact with skin and eyes.
- Do not pour left over paint down any drains.
- **FIRST AID:** If swallowed, give plenty of water to drink and seek medical attention.
If in eyes, rinse with lots of water for at least 15 minutes – seek medical assistance.
If skin contact occurs, wash with warm soapy water – contact a doctor of irritation persists.