

Product Data Sheet

GARDALL® 1000

SACRIFICIAL ANTI-GRAFFITI COATING

DESCRIPTION

- A water based 100% Acrylic Sacrificial Anti Graffiti Coating which can be sprayed or rolled and can be used on many surfaces.

BENEFITS

- Serves as a clear or coloured sacrificial anti graffiti coating preventing penetration of commonly used graffiti marking materials.
- Can be removed through either chemical or hot water blasting techniques.
- Can be over-coated with a non-sacrificial coating (such as Gardall® 2000 or Gardall® 3000 Anti Graffiti Coatings) if required.

RECOMMENDED USE

- Suitable for concrete, limestone, brick, paving, wood surfaces and rigid plastics where a clear (or coloured) topcoat is to be used.

BASIC DATA

- **APPLICATION:** Roller or Airless Spray or Brush to 50 microns WFT
- **COVERAGE:** 10-12 square metres per litre depending on substrate
- **PRIMER:** Not required
- **NUMBER OF COATS:** 2
- **RECOAT:** 3 hours
- **RECOATABILITY:** Yes
- **THINNER:** Up to 10% water on porous substrates
- **DRY TIME:** Touch dry in 3 hours depending on ambient conditions
- **FULL CURE:** 7 days
- **CLEAN UP:** Water with a little detergent, before coating dries
- **GLOSS LEVEL:** Low Sheen
- **COLOURS:** Clear, White and Pastel Colours

SURFACE PREPARATION

- Substrates should be dry and clean with all contaminants such as oil, grease or paint removed by suitable means.
 - The moisture level should be tested with a moisture meter.
- New concrete should have cured for a minimum of 14 days. All laitance, dust and loose materials should be removed. All traces of release agents should be removed before application.
- For old concrete, any contamination should be removed as well as any surface that is loose or damaged.
- **DO NOT APPLY IF SURFACE TEMPERATURE IS LESS THAN 10°C OR IF RAIN IS ANTICIPATED WITHIN 12 HOURS.**

INSTRUCTIONS FOR USE

- Apply two coats of Gardall® 1000 by roller or airless spray or brush.
- Allow 2 hours for coating to dry before applying second coat (more time may be required in cooler or humid conditions).

GRAFFITI REMOVAL

- To remove graffiti we recommend the use of Graffiti Solv graffiti remover.
- Apply Graffiti Solv liberally with a brush, non-atomising sprayer or swab.
- Allow 5-10 minutes contact time for the Graffiti Solv to take effect.
- Using a stiff brush in a circular motion, loosen the graffiti from the surface.
- Remove the graffiti and Gardall® 1000 from the surface with a pressure cleaner.
- Reapply Gardall® 1000 to the surface once dry.

SAFETY

- Ensure adequate ventilation.
- Avoid contact with skin and eyes.
- FIRST AID: If swallowed, induce vomiting, drink plenty of water and seek immediate medical assistance.
If in eyes, rinse with lots of water for at least 15 minutes – seek medical assistance.
If skin contact occurs, wash with warm soapy water – contact a doctor if irritation persists.