

Product Data Sheet

GARDALL[®] ANTI GRAFFITI PRIMER - CLEAR

DESCRIPTION

- A water based 100% Acrylic Sealer which can be sprayed or rolled and can be used on many surfaces.

BENEFITS

- Provides a clear seal for the substrate where the natural colour is required to be maintained.
- Serves as a clear sacrificial anti graffiti coating.
- (When coloured) Provides an easily identifiable coloured primer coat on the substrate.
- Provides a suitable base for use under Gardall[®] 2000 Anti Graffiti Coating.

RECOMMENDED USE

- Suitable for concrete, limestone, brick, paving, wood surfaces and rigid plastics where a clear topcoat is to be used.

BASIC DATA

- **APPLICATION:** Roller or Airless Spray
- **COVERAGE:** 10-12 square metres per litre depending on substrate
- **THINNER:** Up to 10% water on porous substrates
- **CLEAN UP:** Water

SURFACE PREPARATION

- Substrates should be dry and clean with all contaminants such as oil, grease or paint removed by suitable means.
 - The moisture level should be tested with a moisture meter.
- New concrete should have cured for a minimum of 14 days. All laitance, dust and loose materials should be removed.
- For old concrete, any contamination should be removed as well as any surface that is loose or damaged.

INSTRUCTIONS FOR USE

- Apply one coat of Gardall[®] Anti Graffiti Primer (Clear) by roller or airless spray.
- Allow 24 hours for primer to cure.
- Then apply two coats of Gardall[®] 2000 topcoat allowing 4 hours between coats at 25°C.

SAFETY

- Ensure adequate ventilation.
- Avoid contact with skin and eyes.
- **FIRST AID:** If swallowed, induce vomiting, drink plenty of water and seek immediate medical assistance.
If in eyes, rinse with lots of water for at least 15 minutes – seek medical assistance.
If skin contact occurs, wash with warm soapy water – contact a doctor if irritation persists.