

119 Ewing Street, Welshpool WA 6106
Phone 08 9258 7970 Fax 08 9258 9365
E-mail sales@cavalcadecoatings.com.au
Web www.cavalcadecoatings.com.au
A division of Roboyne Pty Ltd ABN 72 150 673 475

## **Product Data Sheet**

# GARDALL® DRIVE-SEAL

#### **DESCRIPTION**

• An ultra-premium grade acrylic based clear coating suitable for use on driveways.

#### **BENEFITS**

- Quick drying to provide a hard wearing finish.
- UV resistant, non-yellowing.
- Very good hot tyre resistance.
- Resists growth of moss and algae.
- Water-based easy clean up and lower odour.

#### **RECOMMENDED USE**

- Recommended for applications where a hard and/or fast drying water-based coating is required.
- Suitable for use on concrete, clay pavers and reconstituted limestone.
- Topcoat sealer for spray-on paving.
- Not recommended for use on timber decking.

#### **BASIC DATA**

• **APPLICATION:** Brush and spray (roller not recommended)

• **COVERAGE RATE:** Approximately 10 square metres per litre – will vary depending

on substrate

• GLOSS LEVEL: Available in Matt

• **THINNER:** Not generally required - up to 10% with water

• CLEAN UP: Water – brushes and spray equipment must be cleaned

immediately with water before the product has a chance to dry.

Clean brushes between coats.

• **RE-COAT:** 20-30 minutes (depending on conditions) – drying time will be

longer in cool/humid conditions

### **SURFACE PREPARATION**

- Surfaces must be clean, dry, and free of dust, grease, oils and wax.
  - A quick check for moisture would be to tape down a small sheet of plastic film onto the substrate – after 1 hour, check for condensation on the underside. If condensation is present, the substrate is too damp to paint.
- DO NOT APPLY IF TEMPERATURE IS LESS THAN 10°C OR GREATER THAN 35°C.

#### **INSTRUCTIONS FOR USE**

- Stir to a consistent viscosity before application.
- Apply 2 coats of Gardall<sup>®</sup> Drive-Seal for best results.

PAGE 1 OF 2



119 Ewing Street, Welshpool WA 6106
Phone 08 9258 7970 Fax 08 9258 9365
E-mail sales@cavalcadecoatings.com.au
Web www.cavalcadecoatings.com.au
A division of Robayne Pty Ltd ABN 72 150 673 475

## **SAFETY**

- Provide adequate ventilation during use.
- Avoid contact with skin and eyes.
- Do not pour left over sealer down any drains.
- FIRST AID: If swallowed, give plenty of water to drink and seek medical attention.

  If in eyes, rinse with lots of water for at least 15 minutes seek medical assistance.

  If skin contact occurs, wash with warm soapy water contact a doctor of irritation