

Product Data Sheet

GARDALL® PAVING SEALER

DESCRIPTION

- An ultra-premium grade acrylic based clear coating.

BENEFITS

- Quick drying to provide a hard water-resistant finish.
- UV resistant, non-yellowing.
- Resists growth of moss and algae.
- Water-based – easy clean up and lower odour.

RECOMMENDED USE

- Recommended for applications where a hard and/or fast drying water-based coating is required.
- Suitable for use on concrete and clay pavers.
- Topcoat sealer for spray-on paving.
- **Not recommended for use on timber decking.**

BASIC DATA

- **APPLICATION:** Brush and spray (roller not recommended)
- **COVERAGE RATE:** Approximately 10 square metres per litre – will vary depending on substrate
- **GLOSS LEVEL:** Available in Gloss and Matt
- **THINNER:** Not generally required - up to 10% with water
- **CLEAN UP:** Water – brushes and spray equipment must be cleaned immediately with water before the product has a chance to dry. Clean brushes between coats.
- **RE-COAT:** 20-30 minutes (depending on conditions) – drying time will be longer in cool/humid conditions

SURFACE PREPARATION

- Surfaces must be clean, dry, and free of dust, grease, oils and wax.
 - A quick check for moisture would be to tape down a small sheet of plastic film onto the substrate – after 1 hour, check for condensation on the underside. If condensation is present, the substrate is too damp to paint.
- **DO NOT APPLY IF TEMPERATURE IS LESS THAN 10°C OR GREATER THAN 35°C.**

INSTRUCTIONS FOR USE

- Apply 2-3 coats of Gardall® Paving Sealer for best results.

SAFETY

- Provide adequate ventilation during use.
- Avoid contact with skin and eyes.
- Do not pour left over paint down any drains.
- **FIRST AID:** If swallowed, give plenty of water to drink and seek medical attention.
If in eyes, rinse with lots of water for at least 15 minutes – seek medical assistance.
If skin contact occurs, wash with warm soapy water – contact a doctor of irritation persists.