

Product Data Sheet

GARDALL[®] TILT SLAB PRIMER

DESCRIPTION

- A clear Acrylic resin solvent-based primer for use on tilt-slab concrete panels that cannot be sand or water blasted prior to painting.

BENEFITS

- Provides a uniform surface for the application of finishing coats that would otherwise be unable to adhere to residual bond-breaker.

RECOMMENDED USE

- Concrete tilt panels.

BASIC DATA

- **APPLICATION:** Can be applied by spray, roller or brush. Apply evenly over the entire surface. When spraying avoid open flames, windy conditions and other situations where over spray may carry onto other surfaces.
Gardall[®] Tilt-Slab Primer should be applied at an ambient temperature in the range of 10°C to 30°C and when rain is not expected within 4 hours of application when applied outdoors.
- **OVERCOATING:** Gardall[®] Tilt-Slab Primer can be re-coated after drying for 1 hour at 25°C.
- **COVERAGE:** Apply at the rate of 15-20 square metres per litre.
- **CLEAN UP:** Use Gardall[®] Tilt Slab Primer Solvent.

SURFACE PREPARATION

- All surfaces must be dry, clean and free from loose materials, dust and mortar droppings.
- Stained, dirty or moss covered surfaces need to be cleaned thoroughly.
- Substrate must be completely dry before applying Gardall[®] Tilt Slab Primer.
 - Check the moisture level with a moisture meter (at the base of the panel). Alternatively, if a moisture meter is not available, a quick check would be to tape down a small sheet of plastic film onto the substrate – after 1 hour, check for condensation on the underside. If condensation is present, the substrate is too damp.

INSTRUCTIONS FOR USE

- Check a small area by spraying lightly with water – if beading occurs, residual bond-breaker is present.
- Apply one coat of Gardall[®] Tilt Slab Primer.

SAFETY

- KEEP OUT OF REACH OF CHILDREN.
- Read the Material Safety Data Sheet.
- Ensure the work area is adequately ventilated. Avoid breathing the vapour or mist spray - wear an approved respirator if working in a confined space.

- Avoid contact with skin and eyes by using gloves and eye protection when pouring or using.
- Keep away from sources of ignition (No smoking or naked flames).
- Do not pour left over paint down any drains. Keep unwanted paint in sealed container for disposal via special waste disposal collections.
- **FIRST AID:** If swallowed, **DO NOT** induce vomiting – give a glass of water and seek immediate medical assistance.
If in eyes, rinse with lots of water for at least 15 minutes – seek medical assistance.
If skin contact occurs, wash with warm soapy water – contact a doctor if irritation persists.