

Product Data Sheet

GARDALL® ULTRASEAL

DESCRIPTION

- A ready for use penetrating stain repellent for use on natural stone and masonry surfaces. Based on fluorocarbon-silane technology it is effective against oil and water-based stains.

FEATURES & BENEFITS

- **Ready for use and fast drying** – easy to apply without messy mixing.
- **Long lasting protection against oil and water-based stains** – ideal for use on a wide range of applications in commercial and domestic situations.
- **Does not change surface appearance** – it retains the original natural look.
- **Bonds chemically to the substrate and cannot peel** – providing long life and hard-wearing performance without the need for frequent recoating.

RECOMMENDED USE

- Concrete and clay pavers, brick, natural stone and masonry surfaces

BASIC DATA

- **APPLICATION:** Can be applied by spray, brush or roller. Apply evenly over the entire surface. When spraying avoid open flames, windy conditions and other situations where over spray may carry onto other surfaces. Apply at an ambient temperature in the range of 10°C to 30°C and when rain is not expected within 4 hours of application when applied outdoors.
- **CURE:** Full cure is achieved in 24 hours, however light foot traffic can be allowed onto treated surface 3 to 4 hours after application.
- **REPAINTING:** Can be re-coated at some future date without any special preparation other than ensuring the surface is clean and dry.
- **COVERAGE:** 2.5–10m² per litre depending on the porosity of the surface being treated.
- **THINNING:** Not required.
- **CLEAN UP:** Gardall® Ultraseal Solvent.

SURFACE PREPARATION

- Ensure the surface to be treated is clean and dry - free from dirt, dust and other contaminants.
- Stained, dirty or moss covered surfaces need to be cleaned thoroughly.
- Damp surfaces need to be dry completely before applying Gardall® Ultraseal.

INSTRUCTIONS FOR USE

- Apply a small test area and check for any discolouration after 24 hours curing.
- Apply one coat of Gardall® Ultraseal evenly over the surface.
- Avoid leaving “puddles” – any excess material should be removed using a clean cloth.
- Do not apply when the substrate temperature is above 35°C.

SAFETY

- Read the Material Safety Data Sheet before use.
- Gardall® Ultraseal releases flammable vapours when curing – take adequate precautions at all times. Avoid sparks and naked flames during and after application.
- Ensure adequate ventilation when using Gardall® Ultraseal.
- Avoid breathing the vapour or mist spray.
- Avoid contact with skin and eyes by using gloves and eye protection when pouring or using Gardall® Ultraseal.
- **FIRST AID:**
 - If swallowed, DO NOT induce vomiting – give a glass of water and seek immediate medical assistance.
 - If in eyes, rinse with lots of water for at least 15 minutes – seek medical assistance.
 - If skin contact occurs, wash with warm soapy water – contact a doctor of irritation persists.