

Product Data Sheet

GEM™ ACRYLIC GLOSS, LOW SHEEN, FLAT

DESCRIPTION

- A premium-grade Gloss, Low Sheen or Flat 100% acrylic based coating suitable for interior and exterior surfaces.

RECOMMENDED USE

- May be used as a decorative and protective coating, particularly suitable for architectural and building construction requirements where a Low Sheen or Gloss or Flat, tough, decorative coating is required.
- Suitable for application to brick, plaster, sand finish, concrete and masonry surfaces, galvanised iron and timber surfaces.

BASIC DATA

- **APPLICATION:** Brush, airless spray or roller.
- **COVERAGE RATE:** Up to 16 square metres per litre depending on substrate.
- **GLOSS LEVEL:** Gloss, Low Sheen or Flat
- **THINNER:** Up to 10% water in 1st coat or warm weather.
- **RECOAT:** 2 hours.
- **CLEAN UP:** Water with a little detergent, before paint dries.
- **COLOUR RANGE:** Full range of colours.

SURFACE PREPARATION

- Surfaces must be clean, dry, and free of dust, grease, oils and wax.
- Loose powdery surfaces should be brushed down thoroughly and sealed with Gem™ All Purpose Sealer prior to application of Gem™ Acrylic Gloss, Low Sheen or Flat.
- **DO NOT APPLY IF SURFACE TEMPERATURE IS LESS THAN 10°C OR IF RAIN IS ANTICIPATED WITHIN 12 HOURS.**

INSTRUCTIONS FOR USE

- On a normal surface apply 1 coat of Gem™ Acrylic Undercoat or Prism™ Prep Coat.
- Then apply 2 coats of Gem™ Acrylic Gloss, Lo Sheen or Flat:
 - First coat may be thinned with up to 10% water.
 - Apply second coat direct from container or thinned with up to 5% water in warm weather.
- **Plaster Walls:** Apply 2 coats directly after recommended primer.
- **Rendered Walls:** Apply 2 coats directly after recommended primer.
- **On Problem Timber (ie bleeding):** Prime first with Gem™ All Purpose Sealer – allow to dry for at least 48 hours. Then 2 coats of Gem™ Acrylic Gloss, Lo Sheen or Flat.
- **Galvanized Surfaces:** Self-priming, apply two coats.

SAFETY

- Ensure adequate ventilation during use.
- Avoid contact with skin and eyes.
- Do not pour left over paint down any drains.
- **FIRST AID:** If swallowed, induce vomiting, drink plenty of water and seek immediate medical assistance.
If in eyes, rinse with lots of water for at least 15 minutes – seek medical assistance.
If skin contact occurs, wash with warm soapy water – contact a doctor if irritation persists.