

Product Data Sheet

GEM™ EASI PAVE

DESCRIPTION

- Gem™ Easi Pave is a polyurethane resin based, low sheen paving paint.
- Good exterior durability and excellent oil and grease resistance.

BENEFITS

- Low sheen, anti-slip finish.
- Quick drying, hard wearing with good resistance to oil and grease.

RECOMMENDED USE

- Suitable for concrete driveways, garage floors and pathways.

BASIC DATA

- **APPLICATION:** Stir paint thoroughly before use using a broad paddle. Product can be rolled or brushed on.
- **COVERAGE RATE:** Approximately 12 – 14 square metres per litre.
- **GLOSS LEVEL:** Low Sheen
- **THINNER:** Up to 10% Mineral Turpentine.
- **CLEAN UP:** Mineral Turpentine.
- **RE-COAT:** 3 Hours at 25°C.
- **COLOUR RANGE:** Available in a range of standard colours.

SURFACE PREPARATION

- **New Concrete** - must be allowed to cure for at least 4 weeks before acid etching and painting.
- **Aged Concrete** (Unpainted) - remove poorly bound or powdery concrete with wire brush before etching.
- **Lightly Stained Areas** – remove all traces of oil, grease etc using a commercial grade concrete cleaner.
- **DO NOT PAINT** over heavily stained, oil impregnated areas that cannot be effectively cleaned. All concrete surfaces **must** be etched to achieve good adhesion.
- **Slipping pathways** may be slippery to walk on when wet and should be mechanically roughened before painting.

INSTRUCTIONS FOR USE

- Apply two coats of Gem™ Easi Pave to a thoroughly prepared dry concrete surface – allowing sufficient time between coats.
 - Surfaces to be painted must be completely dry. A quick check would be to tape down a small sheet of plastic film onto the substrate – after 1 hour, check for condensation on the underside. If condensation is present, the substrate is too damp to paint.
 - First coat may be thinned with 20% Mineral Turpentine to assist penetration.
 - Drying times may be longer in cooler weather.

SAFETY

- KEEP OUT OF REACH OF CHILDREN.
- Read the Material Safety Data Sheet.
- Ensure the work area is adequately ventilated. Avoid breathing the vapour or mist spray - wear an approved respirator if working in a confined space.
- Avoid contact with skin and eyes by using gloves and eye protection when pouring or using.
- Keep away from sources of ignition (No smoking or naked flames).
- Do not pour left over paint down any drains. Keep unwanted paint in sealed container for disposal via special waste disposal collections.
- FIRST AID: If swallowed, DO NOT induce vomiting – give a glass of water and seek immediate medical assistance.
If in eyes, rinse with lots of water for at least 15 minutes – seek medical assistance.
If skin contact occurs, wash with warm soapy water – contact a doctor if irritation persists.