

## Product Data Sheet

# GEM™ GUTTER PRIMER

### DESCRIPTION

- A water-based 100% acrylic resin primer designed for priming galvanised surfaces.

### BENEFITS

- Excellent adhesion to Zinalume® and galvanised surfaces.
- High opacity with good sanding properties.

### RECOMMENDED USE

- Zinalume® gutters and downpipes
- Galvanised metal surfaces.
- May be used on metal door frames.

### BASIC DATA

- **APPLICATION:** Brush or spray.
- **COVERAGE RATE:** Approximately 14 square metres per litre.
- **DRYING TIME:** Approximately 25 minutes.
- **RECOAT:** 2 hours @ 25°C.
- **THINNER:** Water - up to 10% if necessary.
- **CLEAN UP:** Use water with a little detergent to clean equipment before Gem™ Gutter Primer dries.
- **COLOUR RANGE:** White, Charcoal, Red Oxide.

### SURFACE PREPARATION

- Surface should be clean and dry, free from dirt, loose particles, grease and oil.
- New Zinalume® and galvanised surfaces should be wiped down with mineral turpentine using a lint free cloth.

### INSTRUCTIONS FOR USE

- Stir well before use.
- Apply 1 coat of Gem™ Gutter Primer followed by 2 coats of finish for best results.
  - overcoat in 2 hours if using water-based finish or 4 hours if using a solvent-based finish.

### SAFETY

- Ensure adequate ventilation during use.
- Avoid contact with skin and eyes.
- Do not pour left over paint down any drains.
- **FIRST AID:** If swallowed, induce vomiting, drink plenty of water and seek immediate medical assistance.  
If in eyes, rinse with lots of water for at least 15 minutes – seek medical assistance.  
If skin contact occurs, wash with warm soapy water – contact a doctor of irritation persists.