

## Product Data Sheet

# GEM™ SUPER COVER

### DESCRIPTION

- Gem™ Super Cover is a top quality water-based flat ceiling finish suitable for interior use or protected exterior surfaces such as eaves.

### BENEFITS

- Easy to apply.
- Excellent touch-up properties.
- No side sheen.

### RECOMMENDED USE

- Ceilings.
- Eaves.

### BASIC DATA

- **APPLICATION:** Suitable for brush, roller and airless spray
- **COVERAGE RATE:** Approximately 14 square metres per litre - depending upon the surface
- **GLOSS LEVEL:** 2% maximum
- **THINNER:** Up to 10% water in first coat or in warm weather.
- **CLEAN UP:** Water
- **RE-COAT:** After 2 hours.
- **COLOUR RANGE:** White and tintable to pastel shades. Black also available.

### SURFACE PREPARATION

- All surfaces must be clean, dry and free of wax, grease, oils, loose particles and other foreign matter.
- Loose, powdery surfaces should be brushed thoroughly and sealed with Gem™ All Purpose Sealer.

### INSTRUCTIONS FOR USE

- On normal surfaces, apply 2 coats of Gem™ Super Cover.
- On dark substrates, such as cement, apply 1 coat of Gem™ Acrylic Undercoat followed by 2 coats of Gem™ Super Cover.
- Apply Gem™ Super Cover directly from the can – thinning is not normally required.
- Where water stains are present, apply 1 coat of Gem™ All Purpose Sealer and allow to dry for 48 hours before using Gem™ Super Cover.

## SAFETY

- Ensure adequate ventilation during use.
- Avoid contact with skin and eyes.
- Do not pour left over paint down any drains.
- **FIRST AID:** If swallowed, induce vomiting, drink plenty of water and seek immediate medical assistance.  
If in eyes, rinse with lots of water for at least 15 minutes – seek medical assistance.  
If skin contact occurs, wash with warm soapy water – contact a doctor if irritation persists.