

## Product Data Sheet

# K2™ HIGH BUILD SEALER

### DESCRIPTION

- A premium water based Acrylic resin sealer.

### RECOMMENDED USE

- Used as a sealer on cement roof tiles that have deteriorated due to weathering – reduces “shadowing” in the topcoat.

### BASIC DATA

- **APPLICATION:** Suitable for airless spray or brush.
- **COVERAGE RATE:** 5-8 square metres per litre depending on substrate.
- **CLEAN UP:** Water
- **RE-COAT:** Allow 2 hours minimum between K2™ High Build Sealer and K2™ Roof Membrane. Drying time may be longer in cool humid conditions.

### SURFACE PREPARATION

- All surfaces must be water blasted clean, dry and free from dust and dirt.
- Treat surface to be coated with K2™ Bio-Stat – allowing it to dry completely.

### INSTRUCTIONS FOR USE

- **DO NOT APPLY IF SURFACE TEMPERATURE IS LESS THAN 10°C OR IF RAIN IS ANTICIPATED WITHIN 12 HOURS.**
- Apply 1 coat of K2™ High Build Sealer.
- Apply 2 coats of K2™ Roof Membrane to specifications.

### SAFETY

- Ensure adequate ventilation during use.
- Avoid contact with skin and eyes.
- Do not pour left over paint down any drains.
- **FIRST AID:** If swallowed, induce vomiting, drink plenty of water and seek immediate medical assistance.  
If in eyes, rinse with lots of water for at least 15 minutes – seek medical assistance.  
If skin contact occurs, wash with warm soapy water – contact a doctor of irritation persists.