

Product Data Sheet

K2™ ROOF MEMBRANE

DESCRIPTION

- A premium water based 100% Acrylic gloss coating.
- 8 year warranty where complete system is applied and certified by an approved applicator.

RECOMMENDED USE

- Used as a durable rejuvenating gloss finish on roof tiles.
- May also be applied to masonry, Zinalume®, gutters and facias.
- Suitable for use in coastal areas - excellent weather resistance.

BASIC DATA

- **APPLICATION:** Suitable for **airless spray only**.
- **COVERAGE RATE:** 5-8 square metres per litre (airless spray)
- **GLOSS LEVEL:** Gloss
- **THINNER:** Thinning not recommended
- **CLEAN UP:** Water
- **RE-COAT:** Approx. 2 hours depending on humidity and temperature. Drying time will be longer in cool humid conditions.
- **COLOUR RANGE:** Available in a range of standard and Colorbond® colours.

SURFACE PREPARATION

- All surfaces must be water blasted clean, dry and free from dust and dirt.
- Apply K2™ Bio-Stat to the entire surface and allow to dry completely.

INSTRUCTIONS FOR USE

- **DO NOT APPLY IF SURFACE TEMPERATURE IS LESS THAN 10°C OR IF RAIN IS ANTICIPATED WITHIN 12 HOURS.**
- Apply 1 coat of sealer:
 - For previously uncoated surfaces, apply K2™ Sealer or K2™ High Build Sealer (if surface is badly weathered).
 - For previously coated surfaces, apply K2™ Sealer SB.
- Apply 2 coats of K2™ Roof Membrane to specifications.

SAFETY

- Ensure adequate ventilation during use.
- Avoid contact with skin and eyes.
- Do not pour left over paint down any drains.
- **FIRST AID:** If swallowed, induce vomiting, drink plenty of water and seek immediate medical assistance.
If in eyes, rinse with lots of water for at least 15 minutes – seek medical assistance.
If skin contact occurs, wash with warm soapy water – contact a doctor of irritation persists.