

## Product Data Sheet

### K2™ SEALER

#### DESCRIPTION

- A premium water based Acrylic resin clear sealer with excellent adhesion.

#### RECOMMENDED USE

- May be used as a sealer on clay and cement roof tiles and cement render.

#### BASIC DATA

- **APPLICATION:** Suitable for airless spray or brush.
- **COVERAGE RATE:** 5-8 square metres per litre depending on substrate.
- **CLEAN UP:** Water
- **RE-COAT:** Allow 2 hours minimum between K2™ Sealer and K2™ Roof Membrane. Drying time may be longer in cool humid conditions.

#### SURFACE PREPARATION

- All surfaces must be water blasted clean, dry and free from dust and dirt.
- Treat surface to be coated with K2™ Bio-Stat – allowing it to dry completely.
- **DO NOT APPLY IF SURFACE TEMPERATURE IS LESS THAN 10°C OR IF RAIN IS ANTICIPATED WITHIN 12 HOURS.**

#### INSTRUCTIONS FOR USE

- Apply 1 coat of K2™ Sealer.
- Apply 2 coats of K2™ Roof Membrane to specifications.

#### SAFETY

- Ensure adequate ventilation during use.
- Avoid contact with skin and eyes.
- Do not pour left over paint down any drains.
- **FIRST AID:** If swallowed, induce vomiting, drink plenty of water and seek immediate medical assistance.  
If in eyes, rinse with lots of water for at least 15 minutes – seek medical assistance.  
If skin contact occurs, wash with warm soapy water – contact a doctor of irritation persists.