

## Product Data Sheet

# K2™ SOLVENT SEALER

### DESCRIPTION

- A clear Acrylic resin solvent-based sealer for use on roofs which already have an existing coating.

### BENEFITS

- Prevents any inter-coat reactions or blisters.

### RECOMMENDED USE

- Previously coated clay or concrete tiles.

### BASIC DATA

- **APPLICATION:** Can be applied by spray or brush.  
Apply evenly over the entire surface.  
When spraying avoid open flames, windy conditions and other situations where over spray may carry onto other surfaces.  
K2™ Sealer SB should be applied at an ambient temperature in the range of 10°C to 30°C and when rain is not expected within 4 hours of application.
- **REPAINTING:** K2™ Sealer SB can be over-coated after drying for 1 hour at 25°C.
- **COVERAGE:** Apply at the rate of 14-16 square metres per litre.
- **CLEAN UP:** Use K2™ Sealer Solvent.

### SURFACE PREPARATION

- All surfaces must be dry, clean and free from loose materials, dust and mortar droppings.
- Stained, dirty or moss covered surfaces need to be cleaned thoroughly and allow to dry.

### INSTRUCTIONS FOR USE

- Apply 1 coat of K2™ Sealer SB followed by 2 coats of K2™ Roof Membrane.

### SAFETY

- KEEP OUT OF REACH OF CHILDREN.
- Read the material safety data sheet before using.
- Ensure adequate ventilation when using K2™ Sealer SB.
- Avoid breathing the vapour or mist spray – wear an approved organic vapour respirator.
- Avoid contact with skin and eyes by using gloves and eye protection - if contact is made rinse immediately with water. Seek medical advice if swallowed..
- This product is flammable – do not smoke – avoid ignition sources such as naked flames and sparks.
- Do not pour left over paint down any drains. Keep unwanted paint in sealed container for disposal via special waste disposal collections.